25 JAN 2024

2

28 DEC 2023

KWEEN FOUR DEPARTURE (RNAV)

AWOS-3 118.175 CLNC DEL 127.35 UNICOM (CTAF) 122.725 CHARLOTTE DEP CON 128.325 307.8

TOP ALTITUDE: 3000



TAKEOFF MINIMUMS

Rwy 2: Standard.

Rwy 20: 400-234 or standard with minimum climb of 205' per NM to 1300, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 1200' prior to DER.

HMMPY

KWFFN

UNJAM

TASTY

FL180 183° (43)

NOTE: For turbojets only.

NOTE: DME/DME/IRU or GPS required.

NOTE: RNAV 1.

NOTE: RADAR required.

NOTE: If unable to accept climb rates, advise ATC on initial contact.

NOTE: Upon reaching 10000 MSL, accelerate to

and maintain 280K, if unable advise ATC.
NOTE: Transponder code will be issued via PDC

or Charlotte CLNC DEL.

NOTE: Chart not to scale

V


DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 20: Climb heading 202° to 1700 before turning right.

Climb on heading assigned by ATC, expect RADAR vectors to HMMPY, then on track 181° to KWEEN, then on assigned transition, maintain 3000, expect filed altitude within 10 minutes after departure.

PITRW TRANSITION (KWEEN4.PITRW) UNJAM TRANSITION (KWEEN4.UNJAM)

KWEEN FOUR DEPARTURE (RNAV) (KWEEN4.KWEEN) 03JAN19



PITRW